
## TLP-T500U/T501U Series

### Wireless, Robust Multimedia Features and Stunning Brightness



- Brilliant 1,600 ANSI lumens for crisp and colorful display
- Easy to use icon menu for quick and hassle-free setup
- Built-in document camera for captivating 3-D multimedia presentation\* (\*available with TLP-T501U model only)





Models		TLP-T500U	TLP-T501U
Item		XGA Data Projector	
Liquid Crystal Panel Shape 0.9-inch x 3 Aspect Ratio		spect Ratio 4:3	
	No. of Pixels	786,432 (1024 x 768) x 3	
Projection Lens	Standard Lens	1.25x manual zoom/manual focus	
	F/f (mm)	F1.9-2.3, f=35.6-44.5mm	
Light Source		165W high-pressure mercury lamp	
Brightness		1600 ANSI lumens	
Resolution		XGA 1024 x 768	
Color Reproduction		Full-color (16.7M colors)	
Contrast Ratio		400:1	
Projection Screen Size		Approx. 32-300 inches diagonal	
<b>Projection Distance</b>		1.50 to 11.74m	
Compatible Scanning Frequency	Horizontal (kHz)	15-93kHz	
	Vertical (Hz)	50-85Hz	
Video Input Terminals	Video Signals	2 channels (RCA pin x 1, S terminal x 1)	
	Color Difference Signal	2 channels (Mini D-sub 15 pin x 2, shared with RGB signals)	
	Audio Signals	1 channel (RCA x 2)	
RGB Input Terminals	Analogs	2 channels (Mini D-sub 15 x 2 )	
	Audio Signals	1 channel (stereo mini-jack x 1)	
Input Signal Formats	Video Signals	NTSC, PAL. SECAM	
	Color Difference Signal	HDTV&DTV (480i/480p/720p/1080i)	
	RGB Signals	VGA, SVGA, XGA, SXGA, UXGA (compressed)	
Output Terminals	RGB Signals	1 channel (D-sub 15-pin)	
<b>Keystone Correction</b>		Digital (+/- 15 degrees)	
Automatic Keystone		Yes	
Noise Level		35dB (32dB eco-mode)	
Internal Speaker		1W, monaural	
PC Interface		RS-232C (mini DIN-8 pin) USB	
Digital Zoom		Up to x3	
External Dimensions (WxDxH) inch		11.7" W x 9.8" D x 3.8" H	11.7" W x 12.3" D x 3.8" H
Weight (lbs)		7.4	9
Power Consumption (Watt)		240W	240W
Power Source		100-240V, 50/60Hz	
Wireless Technology		IEEE 802.11b	

Document Camera	TLP-T501U	
Image pick-up device	1/3-inch CCD 810,000 pixels	
Resolution	500 TV lines or more (horizontal resolution)	
Camera Lens	F 2.8, f=3.4mm, manual focusing	

#### **Standard Accessories**

Power cord: 3 meter/9.8 feet
RGB cable: 3 meter/9.8 feet
Audio visual cable: 3 meter/9.8 feet
Audio cable: 3 meter/9.8 feet
Audio cable: 3 meter/9.8feet
Mouse remote control with laser pointer
Receiver for the mouse remote control (USB-wireless)
Wireless LAN PC card
Quick Guide
Soft Carry Case
CD-ROM
User's Manual

#### **Limited Standard Warranty:**

2-year on parts and labor including 90-day lamp warranty.

# In Touch with Tomorrow TOSHIBA

Toshiba America Information Systems, Inc. Computer Systems Group P.O. Box 19724, Irvine, California 92623-9724 1-800-TOSHIBA • www.csd.toshiba.com

© 2002 Toshiba America Information Systems, Inc. All other products and names mentioned are the property of their respective owners. All specifications, software, prices and availability are subject to change. All rights reserved.